

**IN THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A vehicle having an internal combustion engine and an axle carrier on which the engine ~~this~~ is mounted, ~~characterized in that~~ wherein the axle carrier (1) has on its top side (4) at least one protective lining (5).
2. (Currently Amended) The vehicle as claimed in claim 1, ~~characterized in that~~ wherein the lining (5) is ~~consists of~~ a material ~~provided~~ with heat-insulating properties.
3. (Currently Amended) The vehicle as claimed in claim 1, ~~either of claims 1 and 2, characterized in that~~ wherein the material of the lining (5) has ~~is equipped with~~ sound-insulating properties.
4. (Currently Amended) The vehicle as claimed in claim 1, wherein ~~one of claims 1 to 3, characterized in that~~ the material of the lining (5) comprises ~~consists of~~ an elastomer-modified thermoplastic, ~~preferably polyamide or polyurethane.~~

5. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 3, characterized in that~~ the material of the lining (5) comprises ~~consists of~~ two interconnected plastics, the one plastic exhibiting sound-insulating properties and the other plastic exhibiting heat-insulating properties.
6. (Currently Amended) The vehicle as claimed in claim 5, ~~characterized in that~~ wherein the plastic having the heat-insulating properties is disposed above the plastic having the sound-insulating properties.
7. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 6, characterized in that~~ wherein the lining (5) covers a track control arm opening (10) in the axle carrier.
8. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 7, characterized in that~~ wherein the lining (5) covers a spring control arm opening (11) in the axle carrier (1).
9. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 8, characterized in that~~ wherein the lining (5) covers an interspace (12) between the axle carrier (1) and a longitudinal member of the vehicle ~~[[,]]~~ to which the axle carrier (1) is fastened.

10. (Currently Amended) The vehicle as claimed in claim 1,  
~~wherein one of claims 1 to 9, characterized in that~~ the  
lining covers a bearing (13) of the axle carrier (1) for an  
axle stabilizer.
11. (Currently Amended) The vehicle as claimed in claim 1,  
~~wherein one of claims 1 to 10, characterized in that~~ the  
linings (5) of the individual cover points are joined  
together in one piece.
12. (Currently Amended) The vehicle as claimed in claim 1,  
~~wherein one of claims 1 to 11, characterized in that~~ the two  
longitudinal sides (3) of the axle carrier (1), extending  
parallel to the vehicle longitudinal axis, are fully covered  
by ~~means of~~ the lining (5), with the exception of the  
fastening points (8)[[,]] for fastening to the longitudinal  
member[[,]] and the engine mount (2).
13. (Currently Amended) The vehicle as claimed in claim 12,  
wherein ~~characterized in that~~ the two lining portions  
covering the longitudinal sides (3) of the axle carrier (1)  
are joined together in such a way that they form a single  
component, the connecting portions fully covering the  
transverse bridges (9) of the axle carrier (1), which join  
its longitudinal sides (3).

14. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 13, characterized in that~~ the lining (5), with the exception of the fastening points (6) for fastening the lining (5) to the axle carrier (1), is distanced from the latter by an air gap (14).
15. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 13, characterized in that~~ the lining (5) is formed by a coating of the axle carrier (1).
16. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 15, characterized in that~~ the lining (5) is of skin-like configuration conforming to the contour of the top side (4) of the axle carrier (1).
17. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 15, characterized in that~~ air chambers are formed on the top side of the lining (5).
18. (Currently Amended) The vehicle as claimed in claim 1, ~~wherein one of claims 1 to 17, characterized in that~~ at points of covered openings (10, 11) in the axle carrier (1), on a circular surface, the lining (5) is provided with diametrical slots (15), with ~~the~~ slotted leaves (16) which are hereupon formed being of resiliently elastic configuration.

U.S. Application No.: NEW  
PRELIMINARY AMENDMENT

Attorney Docket: 3926.103

19. (New) The vehicle as claimed in claim 1, wherein the material of the lining (5) comprises polyamide or polyurethane.